

21-10148 - Soldering Iron Tip, Conical, 0.5 mm



The actual product may differ from image shown

[Add to compare](#)



Manufacturer:	TENMA
Manufacturer Part No.:	21-10148
Newark Part No.:	56T2214
Also Known As:	GTIN UPC EAN: 640522692385
Technical Datasheet:	(EN)

[See all Technical Docs](#)

★★★★★ 5.0 (1) [Write A Review](#)

[Ask A Question](#)

69 In stock

for same day shipping

[see cut-off times](#) ⓘ
[Check stock and lead times](#)

\$3.99
Price for: **Each**
Multiple: **1** Minimum: **1**

Quantity	Price
1 +	\$3.99

[Request a quote for higher quantities](#)

Add **\$50.00** more to your shopping cart to enjoy **FREE SHIPPING**. [Exclusions Apply](#)

Qty

Add to Cart

[Add Line Note](#)

[Add to Fa](#)

Other Items To Consider



Solder Wire, 60/40, 0.031" Diameter 1lb

KESTER SOLDER
24-6040-0027

Price for: Each 1
1+ **\$30.43**

[Add](#)

Hi
JED
My Account

0 item
\$0.00

- Tip / Nozzle Width:** 0.5mm
- Tip / Nozzle Style:** Conical
- For Use With:** Tenma 21-10115, 21-10120, & 21-10130 Soldering Stations
- Product Range:** -

[Find similar products](#)

Choose and modify the attributes above to find similar products.

Product Overview ^

The 21-10148 is a 0.5mm Conical Soldering Tip made of copper and alloy iron coated iron tips perform excellent on temperature between 360 and 380°C. It can only work 4 to 5 hours if tips continuously get heated up beyond 450°C and chrome layer will lose effect if temperature is up to 500°C. It is suitable for use with 21-10115, 21-10120 and 21-10130 soldering stations.

- 0.3µm Alloy iron coating thickness
- 0.2µm Chrome and nickel coating thickness
- Tip length: 17 mm

Applications

Maintenance & Repair

Also Known As ^

GTIN UPC EAN: 640522692385

Customers Also Viewed

TC205
Price for: Each 1
1+ **\$1.30**

[Add](#)



Soldering Iron Tip, Screwdriver, 1.57
WELLER
ETA
Price for: Each 1
1+ **\$4.10**

[Add](#)

Technical Docs

[Technical Data Sheet EN](#)

/

[Operating Instructions EN](#)

Legislation and Environmental

SVHC

To Be Advised

Authorized Distributor